



Cold Climate Case Studies: A Tale of Two Retrofits

Duluth Energy Design Conference
27 February 2013



Rachel Wagner
Wagner Zaun Architecture

In this presentation

1. An integrated approach to retrofits
2. What matters most and why
3. Our Process in 2 case studies
4. Case 1: The Ely Retrofit
5. Case 2: The Superior Retrofit
6. Finding Opportunities

An Integrated Approach

"When we try to pick out anything by itself, we find it hitched to everything else in the Universe." -John Muir

A house rarely needs “just one thing.” And, preparing to “fix” one thing invariably affects other things, so it is better to come prepared to look for and understand the relationships elements have with one another in a building.

(Sound familiar?)

An Integrated Approach

What to consider:

Structure

Skin

Systems

Space

Stuff

Water and air

Living, breathing creatures

Money

An Integrated Approach

So much to consider:

Structure

Skin

Systems

Space

Stuff

Water and air

Living, breathing creatures

Money

Are there priorities even with an integrated approach?

What Matters Most (and why)

1. Safety.
2. Durability.
3. Energy.



What Matters Most (and why)

1. Safety

“Do no harm.”

Take care of the people.

Solve problems that exist.

Do not create new ones.

What Matters Most (and why)

2. Durability

If it lasts, it costs less in the long run.

If it works, it costs less in the long run.

If it is good quality, it adds value and pleasure.

Improving what is already here usually has less negative environmental impact than building something entirely new.

What Matters Most (and why)

3. Energy

Energy efficiency usually increases **comfort**.

Reduced consumption **reduces operating costs**.

Addressing energy use can reduce household environmental impact.

Improving the energy efficiency of the building can mean occupants **stay secure** even when purchased energy is “out of service.”

Approaching what matters most

1. Combustion Safety
2. Ventilation
3. Water Management
4. Air Management (Sealing)
5. Insulation

A word about Radon

TEST

The Process We Used

1. Definition of Goals
2. Assessment of Existing Conditions
3. Analysis of Energy Use/Energy Model
4. Schematic Recommended Approach
5. Modeled Recommended Approach
6. Design
7. Working with the Builder
8. Construction
9. Evaluation and Verification/Lessons

Ely, MN

- 9800 HDD
- 180 CDD
- 1970
- 1-story walk-out
- 3314 ft²
- Septic system
- Lakeshore
- Grid electricity
- Fuel oil
- Firewood



Ely 1. Goals

- Reduce household energy consumption
- Improve household “carbon footprint”
- Improve indoor air quality
- Reduce use of known pollutants
- Maintain most interior finishes
- Improve long term durability
- Fix water management problems

Ely 2. Existing Conditions



This is the “main entry.”

Ely 2. Existing Conditions

- Big masonry chimney that leaked
- Wet basement
- Oil-fired boiler
- New 22.5 kW electric boiler for dual fuel
- Newer electric water heater
- Little opportunity for passive solar gain
- Roof, windows, and siding in need of replacement

Ely 3. Analysis



- Blower door test and infra-red imaging
- REM Design baseline energy model
- Energy consulting
- Existing energy bills
- Exterior approach the obvious choice:
 - Fix bulk water problems
 - Owner wanted to keep interior finishes
 - Exterior finishes at end of useful life

Ely

4. Schematic Approach

- Integrated Thinking
 - Maintaining Priorities
 - Exploring Ideas
 - Conceptual
-
- Intuitive, but with basis in experience

Ely 4. Schematic Approach



Ely 4. Schematic Approach

- HRV and balanced ventilation system
- Remove masonry chimney
- Reduce eaves and simplify roof lines
- Comprehensive air sealing
- Exterior foundation insulation
- Exterior/cavity wall insulation
- Attic and interior ceiling insulation
- New windows
- Create one entry at east gable end


Ely 5. Modeled Approach

- Foundation and rim: R-18 (4" EPS)
- Framed walls: R-34 (9" dense packed cellulose)
- Windows: U-0.19 (Duxton tri-pane)
- Two attic conditions: R-40 and R-60


GOALS:

- Air tightness goal 2.4 ACH50 (50% reduction)
- 65% reduction in heating energy
- 50% reduction in total energy use

Ely 6. Design




BEFORE




AFTER


Ely 6. Design



Ely 6. Design



Ely 6. Design



Removing the chimney helped water management, air sealing, insulation.

Ely 7. Working with the Builder

- Conditions can be messier than imagined
- Builder called when existing conditions varied 😊
- Lots of detail in drawings is great
 - If the builder follows the drawings 😞

Ely 8. Construction



4" EPS foam added to uninsulated foundation walls

Ely 8. Construction



Ely 8. Construction



Second wall framed outside of existing wall.

Ely 8. Construction



Ely 8. Construction



New wall sheathing, and walls insulated (or so we thought).

Ely 9. Evaluation and Verification



If you don't get it right the first time

It is much harder the second time.

A retrofit of a retrofit.

Ely 9. Evaluation and Verification



Actual Energy Use - Ely

<u>Annual Consumption</u>	<u>Before</u>	<u>After</u>
Household Electricity	15,601 kWh	14,278 kWh
Heating - Electricity	69.1 MMBtu	47.1 MMBtu
Heating - Oil	65.4 MMBtu	1.4 MMBtu
Heating - Total	134.5 MMBtu	48.5 MMBtu
	40 kBtu/ft ²	14.6 kBtu/ft ²
Total Site Energy	187.7 MMBtu	97.2 MMBtu
	56.64 kBtu/ft ²	29.33 kBtu/ft ²

Accuracy of Energy Modeling - Ely

	<u>Before</u>	<u>After</u>
<u>Annual Heating Energy</u> Modeled Consumption	149.2 MMBtu	43.2 MMBtu
	45 kBtu/ft ² yr	13 kBtu/ft ² yr
	<u>Before</u>	<u>After</u>
Actual Consumption	134.5 MMBtu	48.5 MMBtu
	40 kBtu/ft ²	14.6 kBtu/ft ²

Ely 9. Lessons Learned

Make things easy to verify.

1. Open up more things before drawing details, even though it can be disruptive.
2. Set “STOP” points if you haven’t worked with Contractor before ... and even if you have.
2. Keep things uncovered where possible (e.g. don’t allow cellulose to be blown into plywood).

Ely 9. Lessons Learned

What I'd do different.

1. Keep existing sheathing on exterior walls. Create the air barrier on the outside of the sheathing, then add Larsen trusses.
2. Net each bay of the Larsen trusses and blow cellulose through fabric.
3. Offer more solutions to reduce household electricity usage.

Superior, WI

- 9800 HDD
- 180 CDD
- 1950 1-story
- 2500 ft²
- Peninsula
- City sewer
- Well water
- Natural gas
- Grid electricity



Superior 1. Goals

- Reduce energy consumption and costs
- Improve comfort
- Improve occupant safety
- Repair/maintain for long-term durability
- Improve delivery of domestic hot water
- Maintain views and ample windows

Superior 2. Existing Conditions

- Prior attic insulation and air sealing work
- Recent kitchen remodel
- Uninsulated slab
- Uninsulated masonry foundation and walls
- Wrecked wood and aluminum windows
- Little opportunity for passive solar gain (missed opportunity!)
- Beautiful views of pines and water

Superior 2. Existing Conditions



- Atmospherically vented boiler and water heater (#1: combustion safety)
- Water piping under slab

Superior 3. Analysis

- Blower door test previously done
- REM Design baseline energy model
- Energy consulting
- Existing energy bills
- Exterior approach chosen:
 - Owner wanted to keep interior finishes
 - Masonry walls and slab = thermal bridges

Superior 4. Schematic Approach

- New boiler and indirect-fired water heater
- New domestic water distribution piping
- HRV and balanced ventilation system
- Replace master bath exhaust fan
- Exterior foundation insulation
- Exterior wall insulation
- Attic insulation where possible
- New windows
- Small entry addition


Superior 5. Modeled Approach

- Foundation: R-20 (4" XPS, fdn wall exterior and horiz skirt)
- Walls: R-24 (4" polyisocyanurate)
- Windows: U-0.23 (Loewen tri-pane)
- Attic: R-50 (blown cellulose over existing fiberglass)

GOALS:

- Air tightness 3 ACH50 (50% reduction)
- 65% reduction in heating energy
- 50% reduction in total energy use



Superior 6. Design



A Simple Plan?

Superior


6. Design



BEFORE

AFTER


Superior 7. Working with the Builder




Investigative
demolition:
Discovering what
we will be getting
into.

Superior

6. Design



BEFORE



AFTER

Superior

8. Construction



Starting from the “bottom up” with insulating foam sheathing.

Superior

8. Construction



Siding over furring over WRB over foam sheathing over existing walls.

Superior 9. Evaluation and Verification



BEFORE



AFTER 51

Actual Energy Use - Superior

	Before: 2009	After: 2011	After: 2012
Electricity	5222 kWh	5647 kWh	5820 kWh
	2.02 kWh/ft ²	2.12 kWh/ft ²	2.18 kWh/ft ²
Natural Gas	212.6 MMBtu	89 MMBtu	77.1 MMBtu
	82 kBtu/ft ²	30 kBtu/ft ²	28.9 kBtu/ft ²
Total Site energy	230.4 MMBtu	108.9 MMBtu	96.3 MMBtu
	89.3 kBtu/ft ²	40.8 kBtu/ft ²	36.1 kBtu/ft ²
Heating Degree Days	8920	9200	7609

Accuracy of Energy Modeling - Superior

	Before	After
Modeled Consumption (heat/DHW)	82.8 kBtu/ft ² yr	35.6 kBtu/ft ² yr
Actual Annual Energy Consumption		
Natural gas (heat/DHW)	82.3 kBtu/ft ² yr	30 +/- kBtu/ft ² yr

Superior 9. Lessons Learned

“Trust but verify”

We should have planned for our own blower door and infrared before and after retrofit.

The “Energy Star provider” was lax.

With Contractor, lines of communication and accountability weren't always clear.

Superior 9. Lessons Learned

What I'd do different

1. Conduct a blower door test at the start. It would have resulted in a slightly different scope of work.
2. Explored options for more natural light into that hallway.
3. Laid out a plan for the eventual roof replacement (and suggest chimney removal).

Opportunities

1. Use “House as a system” thinking.
2. Educate your clients.
3. Offer new ideas and “enhancements.”
4. Present the idea of phased projects.

Opportunities

Rule #1: Learn from your own work.

Rule #2: Learn from others' work.

Opportunities for More Learning

- Fine Homebuilding Energy Smart Homes Winter 2013 special issue



- Journal of Light Construction

- www.greenbuildingadvisor.com

- www.buildingscience.com

- www.affordablecomfort.org

- <http://www1.extension.umn.edu/environment/housing-technology/>



Thank you.

Wagner Zaun
ARCHITECTURE

17 N Lake Avenue
Duluth, MN 55802

218.733.0690

www.wagnerzaun.com